


INDUSTRIAL HOSE CLEANING

CLEAN MASTER™ PRESSURE WASH FORMERLY POWERCLEAN



↔		○	○	⌚	🌊	🧤	🏋️	📏
-size	mm	"	mm	MPa	MPa	mm	kg/100m	REF.
-4	6	1/4	13.5	24.0	90.0	100	23	CLEAN MASTER PRESSURE WASH 3500 1WB 1/4"
-5	8	5/16	15.1	25.0	100.0	130	23	CLEAN MASTER PRESSURE WASH 3600 1WB 5/16"
-5	8	5/16	16.3	35.0	132.0	130	40	CLEAN MASTER PRESSURE WASH 5000 2WB 5/16"
-6	10	3/8	17.2	21.0	84.0	130	33	CLEAN MASTER PRESSURE WASH 3000 1WB 3/8"
-6	10	3/8	18.8	35.0	132.0	130	52	CLEAN MASTER PRESSURE WASH 5000 2WB 3/8"
-5	8	5/16	15.1	25.0	100.0	130	23	CLEAN MASTER PRESSURE WASH 3600B 1WB 5/16"
-5	8	5/16	16.3	35.0	132.0	130	40	CLEAN MASTER PRESSURE WASH 5000B 2WB 5/16"
-6	10	3/8	17.2	21.0	84.0	130	33	CLEAN MASTER PRESSURE WASH 3000B 1WB 3/8"
-6	10	3/8	18.8	35.0	132.0	130	52	CLEAN MASTER PRESSURE WASH 5000B 2WB 3/8"
-8	13	1/2	20.3	17.5	64.0	180	43	CLEAN MASTER PRESSURE WASH 2500B 1WB 1/2"
-8	13	1/2	21.8	28.0	110.0	180	62	CLEAN MASTER PRESSURE WASH 4000B 2WB 1/2"
-6	10	3/8	17.2	21.0	84.0	130	33	CLEAN MASTER PRESSURE WASH 3000G 1WB 3/8"
-6	10	3/8	18.8	35.0	132.0	130	52	CLEAN MASTER PRESSURE WASH 5000G 2WB 3/8"
-8	13	1/2	20.3	17.5	64.0	180	43	CLEAN MASTER PRESSURE WASH 2500G 1WB 1/2"

RECOMMENDED FOR

Use on pressure cleaning equipment. Specially compounded to handle high pressure water service.

TUBE

Type C (Nitrile), black.

REINFORCEMENT

One or two braid of high tensile steel wire.

COVER

C2 (Modified Nitrile). Available in black, blue (B) and grey (G). Blue and grey covers are nonmarking.

TEMPERATURE RANGE

-40°C to +121°C.

STANDARDS

Gates proprietary.

COUPLINGS

MegaCrimp®.

BRANDING TRANSFER LABEL

GATES® CLEAN MASTER™ PRESSURE WASH (2500-5000) NOT FOR STEAM SERVICE MADE IN U.S.A.

IMPORTANT



Not recommended for steam service.