

HIPOL ATF II D

Quality class: GM Dexron®II D

GENERAL FEATURES:

HIPOL® ATF II D is a mineral oil for automatic gears of vehicles.

APPLICATION:

High quality, mineral Hipol® ATF II D oil is intended for application in automatic gears of cars, trucks and buses, manufacturer of which recommends application of Dexron® II D oils. Hipol® ATF II D is also recommended for power steering devices, hydraulic clutches of cars and trucks and for ATF requiring hydraulic systems.

STANDARDS, APPROVALS. SPECIFICATION:

MAN 339 Typ Z1
MAN 339 Typ V1
ZF TE-ML 04D, 11A, 14A
Voith H55.6335xx (G 607)

Meets requirement:

GM Dexron® II D
Allison C-4

PARAMETERS	UNIT	TYPICAL VALUES
Kinematic viscosity at 100°C	mm ² /s	7.26
Kinematic viscosity at 40°C	mm ² /s	35.7
Ignition temperature	°C	208
Resistance to foaming - foam volume after 10 min. standing still at: · at 25°C · at 95°C · at 25°C following the test at 95°C	ml	0 0 0
Corrosiveness to copper 3 h/150°C, corrosion rate, corrosion rate	reference sample	tough

NOTE:
Physicochemical parameters listed in the table are typical values. Real values are stated in quality control certificates attached to each product lot.

